Optical Connector Maker

SOL-1000	
Optical Fiber	SM(G.652 & G.657), MM(G.651), NZDS(G.655), DSF(G.653)
Cable sheath	Round(900um, 2mm, 3mm), Rectangular(2x3mm)
Splicing Loss	0.1dB
Splicing Time	<10sec
Viewing camera	1 axis COMS camera
Battery using time	>100 cycles
Arc cycle	3,000 times
Dimensions / Weight	110(W) x 115(L) x 60(H) mm / 0.65kg

SOL-1000

Applications

- FTTH installation
- Quick connector making

Features

- Non sleeve heater
- Fast connector making
- Low splicing loss
- Small and light

KTC 10339245

Splice On Connector

SOL-100
SOL-200

Connector SOL-100

Kit SOL-200

SOL-100 Connector type

Applications

- FTTH installation
- Quick connector making

Features

- Non sleeve
- Fast wing protector
- Low splicing loss
- Small and light

Splice On Connector	SOL-100	SOL-200
Insertion Loss	<0.1dB	<0.1dB
Return Loss	>45dB(UPC)	>60dB
Cable Sheath	Round(900um, 2mm, 3mm), Rectangular(2x3mm	
Operation Temperature	-40°C to 75°C	-40°C to 75°C
Dimensions	Length = 54.1	51.8 x 8.5 x 7.7 mm

031-450-3450 / y-net.co.kr / 와이넷(주)